

## SCADA Signaling from Badger Flow Meters



**Badger Ultrasonic Flow Meters (pictured left) include the E-Series G2. Badger Also Manufactures Turbine, Positive Displacement, and Magnetic Flow Meters.**



*James Mimplitz, SCADAmetrics – ‘Slim’ Mimplitz*

**Badger Meter** (Milwaukee, Wisconsin, USA) manufactures a broad line of flow meters and AMI/AMR systems, serving the municipal water utility industry. Here at [SCADAmetrics \(Wildwood, MO\)](#), we manufacture flow metering instrumentation in support of this industry, with the stated mission of helping users extend such meters for enhanced SCADA interoperability and functionality.

Like many manufacturers of AWWA-style flow meters, Badger’s signaling options are focused upon their 3-wire, encoded protocol for interfacing with AMI/AMR endpoints. However, Badger also offers pulse and 4-20mA SCADA signaling options, as well. Badger’s 3-wire encoded protocol implementation is capable of transmitting **9-digit, fine-resolution totalization** information — which SCADAmetrics instrumentation leverages to generate additional industrial signal and display options — thereby providing an extended ability to solve the unique challenges facing the **SCADA, Telemetry, and Building Automation spheres**.

The purpose of this document is to provide a summary of several of the main SCADAmetrics devices and methods that we offer to extend the broad line of Badger flow meters.

---

## Badger Compatible Cable Types

Optimal performance is delivered when the most suitable meter signal cable type is provided. Cable types include 3-wire encoded, 2-wire pulse, and in instances where available — *both*.

When encoded cables are utilized, it is always recommended that the Badger meter be pre-programmed to provide the finest resolution available and the maximum number of digits or “wheels” (usually 9 or 8):

### SCADAmetrics Recommendations: Badger Encoded Resolution

Meter Diameter (in)	8-Wheels	9-Wheels
5/8" - 1"	0.1 USG 0.01 FT3 0.1 L	0.01 USG 0.001 FT3 0.01 L
1.5" - 4"	1 USG 0.1 FT3 1 L	0.1 USG 0.01 FT3 0.1 L
6" - 12"	10 USG 1 FT3 10 L	1 USG 0.1 FT3 1 L

When pulse cables are utilized, it is always recommended that the Badger meter be pre-programmed to provide the finest resolution pulse available:


### SCADAmetrics Recommendations: Badger Pulse Option

Meter Diameter (in)	Pulse Weight
5/8" - 1"	0.1 USG 0.01 FT3 0.1 L
1.5" - 4"	1 USG 0.1 FT3 1 L
6" - 12"	10 USG 1 FT3 10 L

---

# 1. Concurrent Basic SCADA and AMI from Encoded-Only Flow Meter

The following illustrates how a model EMP Signalizer display can be paired with an encoded-only Badger flow meter to provide basic SCADA signaling, while preserving the existing AMI signaling to the water utility. The SCADA signaling is in the form of a 4-20 milliamp output, a pulse-per-volume output, and a meter fault alarm output. Please note that the 4-20 milliamp SCADA output requires a 8/9-digit encoded signal from the meter. Excellent for custody-transfer stations. Also excellent for utility-owned water meters at commercial and industrial buildings, where the building owner desires a meter reading into its BMS system, without requiring the installation of a new water meter, or without interfering with the utility's AMI system. Design Basis: SCADAmetrics [Model EMP Signalizer](#):




## SCADAmetrics Recommendations: Badger Encoded Resolution

Meter Diameter (in)	8-Wheels	9-Wheels
5/8" - 1"	0.1 USG 0.01 FT3 0.1 L	0.01 USG 0.001 FT3 0.01 L
1 1/2" - 4"	1 USG 0.1 FT3 1 L	0.1 USG 0.01 FT3 0.1 L
6" - 12"	10 USG 1 FT3 10 L	1 USG 0.1 FT3 1 L

## 2. Concurrent Basic SCADA and Remote Display from Encoded-Only Flow Meter

The following illustrates how an encoded-only Badger flow meter can provide basic SCADA signaling (4-20 milliamp, pulse-per-volume, meter fault alarm), and a Remote Wall Display. Excellent for custody-transfer stations and commercial buildings. Design Basis: [Model EMP Signalizer](#) and [Model TMD TheMeterDisplay](#). Coming soon! — TMD Support for Badger E-Series advanced alarm flags (Temperature & Pressure).




### SCADAmetrics Recommendations: Badger Encoded Resolution

Meter Diameter (in)	8-Wheels	9-Wheels
5/8" - 1"	0.1 USG 0.01 FT3 0.1 L	0.01 USG 0.001 FT3 0.01 L
1 1/2" - 4"	1 USG 0.1 FT3 1 L	0.1 USG 0.01 FT3 0.1 L
6" - 12"	10 USG 1 FT3 10 L	1 USG 0.1 FT3 1 L

### 3. Concurrent Basic SCADA, AMI, and Remote Display from Encoded-Only Flow Meter

The following illustrates how an encoded-only Badger flow meter can provide basic SCADA signaling (4-20 milliamp, pulse-per-volume, meter fault alarm), AMI signaling (3-Wire Encoder Protocol), and a Remote Wall Display. Excellent for custody-transfer stations and commercial buildings. Design Basis: [Model EMP Signalizer](#) and [Model TMD TheMeterDisplay](#). Coming soon! — TMD Support for Badger E-Series advanced alarm flags (Temperature & Pressure).



## 4. Advanced SCADA from Encoded Flow Meter

The gold standard of SCADA connectivity for a flow meter is transmission of the “true” meter reading into the SCADA system with zero error. We call that “revenue-grade accuracy”. The following illustrates how a Badger flow meter can be enhanced to provide advanced SCADA signaling (Modbus, Allen-Bradley EtherNet/IP). Excellent for custody-transfer pumping and valve stations where revenue-grade accuracy is of paramount importance. Also excellent for military bases and educational facilities. Design Basis: [Model EM.100 EtherMeter](#):

Model EM100  
by SCADAmetrics  
“EtherMeter®”




SCADA System

Totalizer Reading Received by SCADA System Perfectly Matches Badger Meter Register.

Modbus/TCP  
Allen-Bradley EtherNet/IP

Modbus/RTU  
Allen-Bradley DF1  
(RS.485)

3-Wire Encoded Cable




SCADAmetrics Recommendations:  
Badger Encoded Resolution

Meter Diameter (in)	8-Wheels	9-Wheels
5/8" - 1"	0.1 USG 0.01 FT3 0.1 L	0.01 USG 0.001 FT3 0.01 L
1 1/2" - 4"	1 USG 0.1 FT3 1 L	0.1 USG 0.01 FT3 0.1 L
6" - 12"	10 USG 1 FT3 10 L	1 USG 0.1 FT3 1 L


## 5. Concurrent Advanced SCADA and AMI from Encoded Flow Meter

The gold standard of SCADA connectivity for a flow meter is transmission of the “true” meter reading into the SCADA system with zero error. We call that “revenue-grade accuracy”. The following illustrates how a Badger flow meter can be enhanced to provide advanced SCADA signaling (Modbus, Allen-Bradley EtherNet/IP), while at the *same time* provide signaling to a connected AMI System. Excellent for custody-transfer metering, pumping, and valve stations where revenue-grade accuracy is of paramount importance for both the SCADA system and AMI system. Also excellent for commercial and industrial facilities who wish to internally track the utility-owned water meter. The inclusion of a model SDA or SDAW Duplexer (illustrated below) ensures concurrent AMI connectivity. Design Basis: [Model EM.100 EtherMeter](#) and [Model SDA SCADA Duplexer for AMI](#):



## 6. Basic SCADA from Encoded-Only Flow Meter

The following illustrates how an encoded-only Badger flow meter can provide basic SCADA signaling (4-20 milliamp, pulse-per-volume, meter fault alarm). Excellent for well and pumping stations, as well as commercial building submetering. Design Basis: [Model EMP Signalizer](#):




### SCADAmetrics Recommendations: Badger Encoded Resolution

Meter Diameter (in)	8-Wheels	9-Wheels
5/8" - 1"	0.1 USG 0.01 FT3 0.1 L	0.01 USG 0.001 FT3 0.01 L
1 1/2" - 4"	1 USG 0.1 FT3 1 L	0.1 USG 0.01 FT3 0.1 L
6" - 12"	10 USG 1 FT3 10 L	1 USG 0.1 FT3 1 L

## 7. Basic SCADA Outputs from Pulse Flow Meter

The following illustrates how a Badger pulse-type flow meter can provide basic SCADA signaling (4-20 milliamp, pulse-per-volume, flow switch, meter fault alarm). Excellent for well and pumping stations and commercial submetering. Design Basis: SCADAmetrics [Model APK Analog-Pulse Kit](#):



## 8. Visual Batching, Visual Rate-of-Flow, plus SCADA Outputs from Pulse Flow Meter

The following illustrates how a Badger pulse-type flow meter can provide basic SCADA signaling (4-20 milliamp, pulse-per-volume, flow switch, meter fault alarm), along with an always-ON operator flow and batch display. Excellent for well and pumping stations. Design Basis: SCADAmetrics [Model APK.PLUS Analog-Pulse Kit, Plus](#):



MODEL APK PLUS by SCADAmetrics "Analog Pulse Kit"



FROM EXTERNAL 24Vdc POWER ADAPTER.

+24Vdc  
DC Common

2-Wire Pulse Output (Dry Contact)

4-20mA + Output 1  
Pulse per Volume (Dry Contact)  
Flow Switch (Dry Contact)

Signals to SCADA/Telemetry system

### SCADAmetrics Recommendations: Badger Pulse Option

Meter Diameter (in)	Pulse Weight
5/8" - 1"	0.1 USG 0.01 FT <sup>3</sup> 0.1 L
1.5" - 4"	1 USG 0.1 FT <sup>3</sup> 1 L
6" - 12"	10 USG 1 FT <sup>3</sup> 10 L


BADGER FLOW METER WITH SCALED PULSE



HR REGISTERS


## 9. Basic SCADA plus AMI from a Dual-Output Flow Meter (Encoded+Pulse)

The following illustrates how a Badger dual-output flow meter (encoded+pulse) can provide basic SCADA signaling (4-20 milliamp, pulse-per-volume, flow switch, meter fault alarm) — and concurrent AMI capability. Excellent for well and pumping stations and custody-transfer stations. Design Basis: SCADAmetrics [Model APK Analog-Pulse Kit](#):




## 10. Visual Batching, Visual Rate-of-Flow, plus SCADA Outputs from Dual-Output (Encoded+Pulse) Meter

The following illustrates how a Badger dual-output (encoded+pulse) flow meter can provide basic SCADA signaling (4-20 milliamp, pulse-per-volume, flow switch, meter fault alarm), along with an always-ON operator flow and batch display — and concurrent AMI capability. Excellent for well and pumping stations and custody-transfer stations. Design Basis: SCADAmetrics [Model APK.PLUS Analog-Pulse Kit, Plus](#):



# 11. Basic SCADA plus Remote Display plus AMI from a Dual-Output Flow Meter (Encoded+Pulse)

The following illustrates how a Badger dual-output flow meter (encoded+pulse) can provide basic SCADA signaling (4-20 milliamp, pulse-per-volume, flow switch, meter fault alarm) — and concurrent AMI capability. Excellent for well and pumping stations and custody-transfer stations. Design Basis: SCADAmetrics [Model APK Analog-Pulse Kit](#):



## 12. Dual-AMI Connectivity

The following illustrates how a Badger flow meter can provide AMI signaling to two separate systems. Excellent for custody-transfer stations, where both the water buyer and seller desire meter connectivity to their separate respective AMI systems. Design Basis: SCADAmetrics [Model UDA Universal Duplexer for AMI](#):


**BADGER  
ORION**

**Model UDA  
Universal Duplexer**

**AMI #2**




**BADGER  
ENCODER-TYPE  
FLOW METER**



**HRE  
REGISTERS**

### 13. Concurrent AMI Connectivity and Remote Visual Display

The following illustrates how a model TMD display can work with a Badger flow meter to provide AMI signaling to the water utility, while concurrently providing a visual remote display whose reading is a perfect match to the Badger meter register total. Furthermore, if the Badger register is programmed for 8 or 9 digit resolution, then this fine resolution will enable the display of rate-of-flow (GPM, lpm), as well. Excellent for utility-owned water meters at commercial and industrial buildings, where the building owner desires a meter reading without requiring entry to a vault or confined-space. Design Basis: SCADAmetrics [Model TMD TheMeterDisplay](#). Coming soon! — TMD Support for Badger E-Series advanced alarm flags (Temperature & Pressure).



**SCADAmetrics Recommendations:  
Badger Encoded Resolution**

Meter Diameter (in)	8-Wheels	9-Wheels
5/8" - 1"	0.1 USG 0.01 FT3 0.1 L	0.01 USG 0.001 FT3 0.01 L
1.5" - 4"	1 USG 0.1 FT3 1 L	0.1 USG 0.01 FT3 0.1 L
6" - 12"	10 USG 1 FT3 10 L	1 USG 0.1 FT3 1 L

## 14. Remote Visual Display

The following illustrates how a model TMD display can work with a Badger flow meter to provide a remote visual display to an otherwise not-easily accessible water meter. The remote display provides a perfect match to the reading displayed on the Badger meter register. Furthermore, if the Badger meter register is programmed for 8 or 9 digit resolution, then this fine resolution will enable the display of rate-of-flow (GPM, lpm), as well. Excellent for customer-owned sub-meters at commercial and industrial buildings, where the building owner desires a meter reading without requiring entry to a vault or confined-space. Design Basis: SCADAmetrics [Model TMD TheMeterDisplay](#). Coming soon! — TMD Support for Badger E-Series advanced alarm flags (Temperature & Pressure).

**MODEL TMD  
by SCADAmetrics  
TheMeterDisplay**



**BADGER  
ENCODER-TYPE  
FLOW METER**



**SCADAmetrics Recommendations:  
Badger Encoded Resolution**

Meter Diameter (in)	8-Wheels	9-Wheels
5/8" - 1"	0.1 USG 0.01 FT3 0.1 L	0.01 USG 0.001 FT3 0.01 L
1 1/2" - 4"	1 USG 0.1 FT3 1 L	0.1 USG 0.01 FT3 0.1 L
6" - 12"	10 USG 1 FT3 10 L	1 USG 0.1 FT3 1 L

**HRE  
REGISTERS**



## 15. Connect Pulse Flow Meters to Badger Orion AMI

The Pulse Encodalizer is a battery-powered signal converter with integral 9-digit display. It counts pulses from most 2-wire, pulse-type flow meters (magmeters, wastewater meters, gas meters, steam meters, reclaimed water meters, irrigation meters, etc...) — and converts to a 3-Wire Encoded protocol — thereby providing compatibility with Badger's Orion AMI system. Badger's lineup of magmeters already feature encoded outputs, so the Encodalizer is not needed for those. However, there are a large number of 3rd-party pulse type meters that can benefit from the Encodalizer, whose battery pack offers a life up to 10 years and is user-replaceable.

The following illustrates how a model PTE Pulse Encodalizer™ can transform a pulse-type flow meter into an Orion-compatible encoder-type flow meter. Excellent for wastewater lift stations, irrigation points-of-sale, sewer deduct meters, natural gas meters. Design Basis: SCADAmetrics [Model PTE Pulse Encodalizer](#):



### Want to Learn More?...

Are you interested in learning more about how SCADAmetrics flow instrumentation, when paired with Badger flow meters, can provide a wealth of value-added SCADA and visual display options? Give us a call!... We'll be glad to discuss the details!